SERIES 41 MANIFOLDS °F and °C with 2-1/2" (63.5 mm) gauges



Forged body is solid brass for durability. Full porting maximizes capacity. Metal valve handles are full size for easy operation. Hose anchors are forged into back of body at 45°.

- Flutterless[™] technology means surge protector and silicone dampened movement helps minimize needle pulsation for easier, more accurate readings
- Sliding double "O" ring pistons reduces wear
- Most manifolds include color-coded YELLOW JACKET charging hoses
- Easy-to-read 2-1/2" (63.5 mm) steel case gauges with 3-2-3% accuracy (Class B)
- Limited lifetime warranty on manifold bar and valves – not gauges. See warranty information for details
- Made in the USA



Series	41 Manifolds		
UPC#	Description - °F and °C - Red/Blue	Scale	Refrigerant
42051	Heat pump manifold only, 1/4-5/16-1/4"	bar/psi	
42054	With 60" black PLUS II hoses (two 1/4x5/16" ball valve and one 1/4x1/4" ball valve)	bar/psi	R-410A
41712	Manifold only	kg/cm²/psi	
41703	With 60" PLUS II [™] compact ball valve fittings	kg/cm²/psi	
41709	With 60" PLUS II [™] standard fittings	kg/cm²/psi	
41715*	With 60" PLUS II [™] standard fittings	kg/cm²/psi	R-410A
41710	With 60" PLUS II [™] heavy duty black standard fittings	kg/cm²/psi	n-410A
41702	With 60" PLUS II [™] heavy duty black compact ball valve fittings	kg/cm²/psi	
42715	With 60" PLUS II [™] compact ball valve fittings	kg/cm²/psi	
41711*	With 60" PLUS II [™] compact ball valve fittings	kg/cm²/psi	
41652	Manifold only with 5/16, 1/4", 5/16" hose fittings	bar/psi	R-32/410A
UPC#	Description - °F - Red/Blue	Scale	Refrigerant
41212	Manifold only	psi	
41213	With 36" PLUS II [™] standard fittings	psi	
41220	With 48" PLUS II [™] standard fittings	psi	
41215	With 60" PLUS II [™] standard fittings	psi	
41219	With 72" PLUS II [™] standard fittings	psi	
44213	With 36" <i>PLUS II</i> [™] SealRight fittings	psi	R-12/22/502
44220	With 48" <i>PLUS II</i> [™] SealRight fittings	psi	
44215	With 60" PLUS II [™] SealRight fittings	psi	
44219	With 72" PLUS II [™] SealRight fittings	psi	
42215	With 60" <i>PLUS II</i> [™] compact ball valve fittings	psi	
42219 41312	With 72" <i>PLUS II</i> [™] compact ball valve fittings Manifold only	psi	
41312	With 36" <i>PLUS II</i> [™] standard fittings	psi psi	
41313	With 48" <i>PLUS II</i> [™] standard fittings	psi	
41315	With 60" <i>PLUS II</i> [™] standard fittings	psi	
41319	With 72" <i>PLUS II</i> [™] standard fittings	psi	
43313	With 36" PLUS II [™] standard fittings	psi	
44313	With 36" <i>PLUS II</i> [™] SealRight fittings	psi	R-134a/404A/507
44315	With 60" <i>PLUS II</i> [™] SealRight fittings	psi	
44319	With 72" PLUS II [™] SealRight fittings	psi	
42315	With 60" PLUS II [™] compact ball valve fittings	psi	
41202	Manifold only	psi	
41209	With 36" PLUS II [™] standard fittings	psi	R-22/134a/404A
41211	With 60" PLUS II [™] standard fittings	psi	
UPC#	UPC# Description - °C - Red/Blue	Scale	Refrigerant
42008	Manifold only	bar/psi	
41283	With 36" PLUS II [™] standard fittings	bar/psi	
41285	With 60" PLUS II [™] standard fittings	bar/psi	
42002	Manifold only	kPa/psi	
41223	With 36" PLUS II [™] standard fittings	kPa/psi	R-12/22/502
41225	With 60" <i>PLUS II</i> [™] standard fittings	kPa/psi	
41292	Manifold only	kg/cm ² /psi	
41293	With 36" <i>PLUS II</i> [™] standard fittings	kg/cm²/psi	
41295 41299	With 60" <i>PLUS II</i> [™] standard fittings With 72" <i>PLUS II</i> [™] standard fittings	kg/cm ² /psi	
41299	Manifold only	kg/cm²/psi bar/psi	
41353	With 36" <i>PLUS II</i> [™] standard fittings	bar/psi	
41355	With 60" <i>PLUS II</i> [™] standard fittings	bar/psi	
43355	With 60" <i>PLUS II</i> [™] standard fittings	bar/psi	
41392	Manifold only	kg/cm²/psi	R-134a/404A/507
41363	With 36" PLUS II [™] standard fittings	kg/cm²/psi	
41365	With 60" <i>PLUS II</i> [™] standard fittings	kg/cm²/psi	
43365	With 60" <i>PLUS II</i> [™] standard fittings	kg/cm²/psi	
41332	Manifold only	bar/psi	R-134a/404A/407C
40944	Manifold only with 1/4" ports and 5/16" hose fittings	bar/MPa	R-410A
41781	Manifold only with 5/16" fittings	bar/MPa	11-410/4
41780	Manifold only with 1/4" fittings	bar/MPa	
*Specia	R-410A hose - R/B hoses are 1/4" x 45° 5/16" end; Y hose is 1/4" x 45° 1/4" end.		

RECOVERY MACHINES

SYSTEMS

VACUUM AND HOS CHARGING HOSES VALVI

HOSE ADAPTERS, VALVES AND PARTS

CHARGING

GAUGES

WIRELESS AND ELECTRONIC INSTRUMENTS

> HEATING INSTRUMENTS

> AND DETECTORS

SYSTEM TOOLS