

CEILING & FLOOR CONVERTIBLE

STANDARD INVERTER (R410A)

CV09
CV12



LG participates in the ECP programme for EUROVENT AC program.
Check ongoing validity of certification
: www.eurovent-certification.com

UU09W / UU12W



INDOOR				CV09 NE2	CV12 NE2
Capacity	Cooling	Min / Nom / Max	kW	1.0 / 2.5 / 2.8	1.3 / 3.3 / 3.6
	Heating	Min / Nom / Max	kW	1.2 / 3.0 / 3.3	1.5 / 3.8 / 4.2
Low Temperature Capacity	Heating -7°C	Max	kW	3.1	3.4
	Cooling	Nom	kW	0.75	1.09
Power Input (Set)	Heating	Nom	kW	0.83	1.18
		Nom	W	30	40
Running Current	Cooling / Heating	Nom	A	3.26 / 3.61	4.74 / 5.13
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50
EER				3.33	3.03
COP				3.61	3.22
SEER				5.11	5.31
SCOP				3.81	3.81
Pdesign (@ -10°C)			kW	3.0	3.0
Seasonal Energy Label	Cooling / Heating			A / A	A / A
Annual Energy Consumption	Cooling / Heating		kWh	172 / 1,102	218 / 1,102
	Liquid		mm (inch)	Ø6.35 (1/4)	Ø6.35 (1/4)
Piping Connection	Gas		mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)
	Drain	O.D. / I.D.	mm	21.5 / 16.0	21.5 / 16.0
Air Flow Rate		High / Medium / Low	m³/min	7.6 / 6.9 / 6.2	9.2 / 7.6 / 6.6
Sound Pressure	Cooling	High / Medium / Low	dBA	38 / 35 / 32	40 / 36 / 31
Sound Power	Cooling	Max	dBA	52	56
Dehumidification Rate			l/h	1.2	1.2
Dimensions	Body	W x H x D	mm	900 x 490 x 200	900 x 490 x 200
Net Weight	Body		kg	13.7	13.7
List Price			£	£392.00	£404.00

OUTDOOR				UU09W ULO	UU12W ULO
Compressor	Type			Rotary	Rotary
Airflow Rate		Nom	m³/min	32	32
Sound Pressure	Cooling	Nom	dBA	47	47
	Heating	Nom	dBA	48	48
Sound Power	Cooling	Max	dBA	56	57
Dimensions	W x H x D		mm	770 x 540 x 245	770 x 540 x 245
Net Weight			kg	32.0	32.0
Refrigerant	Type		-	R410A	R410A
	Charge		g	1,000	1,000
	Additional Charge		g/m	20	20
	GWP		-	2,087.5	2,087.5
	TCO2eq		-	2.1	2.1
Operation Range (Outdoor)	Cooling	Min ~ Max	°C DB	-10 ~ 43	-10 ~ 43
	Heating	Min ~ Max	°C WB	-18 ~ 18	-18 ~ 18
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable			No. x mm²	3C x 2.5	3C x 2.5
Transmission Cable			No. x mm²	4C x 0.75	4C x 0.75
Circuit Breaker			A	15	15
Piping Length Total		Min ~ Max	m	5~15	5~15
Piping Elevation Difference	IDU - ODU	Max	m	10	10
Piping Connection	Liquid		mm (inch)	Ø6.35 (1/4)	Ø6.35 (1/4)
	Gas		mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)
List Price			£	£697.00	£720.00

Note: 1. Due to our policy of innovation some specifications may be changed without notification.

2. Definition of Power Input Nominal conditions - Performance tested under EN14511

3. Capacities are based on the following conditions:

Cooling: - Indoor Temperature 27°C DB / 19°C WB - Outdoor Temperature 35°C DB / 24°C WB Heating: - Indoor Temperature 20°C DB / 15°C WB - Outdoor Temperature 7°C DB / 6°C WB

4. Annual energy consumption: based on average use of 350 running hours in cooling and 1,400 hours in heating per year at seasonal condition

5. This product contains fluorinated greenhouse gases (R410A)